

# Microtill Pad

## Maintaining Water and Dust Protection

### What is an IP rating and what does it mean for your Microtill Pad:

An IP (Ingress Protection) rating is an international standard that shows you the level of ingress protection of your Microtill Pad. Our Microtill Pad device have been certified to an IP68 rating. The Microtill Pad is built to do more, in more places. With an IP68 rating, they're water resistant to a maximum depth of 1.5m for up to 30 minutes, and is protected from dust, dirt and sand - all without the need for extra caps or covers. Now there's less to worry about. You can enjoy more freedom to explore, stay connected, and capture the adventure.

### How to properly care for and use your Microtill Pad:

The Microtill Pad may be damaged if water or dust enters the device. Follow these tips carefully to prevent damage to the device and to help maintain the water and dust-resistant performance of the Microtill Pad.

- Do not immerse the Microtill Pad in water deeper than 1.5 metres and do not keep it submerged in water less than 1.5 metres deep for more than 30 minutes.
- Do not expose the Microtill Pad to water moving with force, such as water running from a tap, ocean waves, or waterfalls.
- If the Microtill Pad is exposed to freshwater, dry it thoroughly with a clean, soft cloth. If the Microtill Pad is exposed to any liquid other than freshwater, gently rinse the device with still fresh water immediately and dry it thoroughly with a clean soft cloth. Failure to gently rinse the device in still fresh water and dry it as instructed may cause Microtill Pad to suffer from operability or cosmetic issues.
- If the Microtill Pad is dropped or receives an impact, the water and dust-resistant features of the device may be damaged.
- The touch screen and other features may not work properly while the Microtill Pad is in water.

The Microtill Pad has been tested in a controlled environment and certified to be protected against water and dust ingress in specific situations (meets requirements of Classification IP68 as described by the International Standard IEC 60529 – Degrees of Protection provided by Enclosures [IP Code]; test conditions: 15-35oC, 86 – 106kPa, 1.5 metres, 30 minutes).

Please follow the instructions outlined above to maintain the water and dust resistant performance of your Microtill Pad.